



# S660 DVB-S2 USB Specification

- Low power consumption DVB-S2 chips
- Bundled software myTeVii
- Trial version ProgDVB Pro
- Bundled IP software TeViiData



## Software Key Features

- Watch DVB-S/S2 TV and Radio on PC
- Support HDTV (MPEG-4 AVC/ H.264 up to 1080i)
- Blind Scan
- Real-time recording in MPEG/TS format
- DVB Electronic Program Guide (EPG)
- Transponder / satellite auto scan
- Time-Shifting
- Teletext
- Subtitles
- Support DiSEqC1.2 & USALS
- Full screen display / On screen display (OSD)
- Remote control supported
- DVB core based plug in supported
- Linux driver supported
- English/Russian/German/French and multi-languages supported

## Tuner

- Input terminal: F-type 75 Ohm
- Receiving frequency: 950~2150 MHz tuning range



# S660 DVB-S2 USB Specification

- Input level: :-65~25 dbm

## LNB & Switch Control

- Antenna and LNB control: 22KHz tone
- DiSEqC:1.2 & USALS
- LNB Supply Voltage:13 or 18V
- Max.LNB Supply Current:400MA with Short Circuit Protection

## USB Interface

- Bus: Universal Serial Bus 2.0 Standard
- Mini USB connector

## Package Includes

- S660 DVB-S2 USB box
- Power adapter
- Remote control
- USB cable
- Installation CD
- Quick Installation Guide (English & German)

## System Requirements

- Microsoft Windows XP/Vista
- 2.0GHz CPU (2.4GHz for HDTV)
- 256M RAM (1GB for HDTV)
- VGA card with at least 128MB memory
- Microsoft Direct X 9.0C or above
- Sound card or on-board sound chip
- One free USB port
- Digital satellite dish & LNB



# S660 DVB-S2 USB Specification